

## Industrial Grade Super Large Load Dustproof & Waterproof



## Unitree

Parameter		B1
Image		
Product Parameters	Size(Standing)	1126mm×467mm×636mm
	Weight (With Battery)	55kg
	Ingress Protection	IP68 (optional) IP67 (standard)
	Endurance Time	2–2.5h
	Max Walking Load (Payload)	20kg
	Max Standing Load	80kg
	Max Walking Speed	1.2m/s
Obstacle Crossing Ability	Stairways	20cm
	Slopes	30°
Perception System	Perceptual Controller	Jetson Xavier NX*3
	Down Looking Terrain Direct Sensing Sensor	•
	Look Around Terrain Direct Sensing Sensor	•
Product Configuration	Wireless Vector Positioning Technology	•
	Max Instantaneous Torque Of Knee Joint	210N.m
	Gigabit Network Port	•
Functions & Equipment	5G wireless network communication, GNSS acquisition (GPS, Beidou, etc.), over-the-horizon communication.	Standard Configuration
	Smart manipulator, autonomous charging pile, PTZ camera, security patrol mounting platform, emergency rescue mounting platform.	Optional
Application	EXPLORATION DETECTION	RITY OL EMERGENCY RESCUE

\*This manual will be modified appropriately according to product improvement, specification change and other reasons without additional notice.